



HAYAT AL MAJD  
حيات المجد

*Trusted global trading company specializing in the procurement and distribution of high-quality oil and petrochemical products*

# SPECIFICATIONS OF VG-30 BITUMEN

Grade/Product Name

Property	Unit	Typical Data	Test Methods
Absolute Viscosity at 60	°c	Min.2400	IS 1206 (Part2)
Kinematic Viscosity at 135°c	cSt	Min. 350	IS 1206 (part3)
Flash Point (Cleveland Open Cup)	c°	Min.220	IS 1209
Solubility in Trichloroethylene	%wt	Min.99	IS 1206
Softening Point (R&B)		Min. 47	IS 1205
Penetration@ 25°c,100gm,5secs	0.1mm	50-70	IS 1203
<b>Testson Residue from Thin Film Oven Tests / RTFOT</b>			
Viscosity Ratio at 60	°c	Max. 4.0	IS 1206 (Part2)
Ductility at 25°c,cm.after Thin-Film Oven Test	cm	Min. 40	IS 1208
Specific Gravity @ 27/27	°c	Min.0.99	IS 1202

*Hayat Al Majd General Trading Co.*

+971 50 895 5353

info@hayatco.co

www.hayatco.co

406, Business Port, Port Saeed, Deira, Dubai